

SAFATEX Linear Lights

Models Available: 36W and 60W

The SAFATEX liner range is a explosion proof light fittings suitable for surface mounted in zones 1, 2, 21 & 22 hazardous areas and is an ideal replacement for fluorescent light fittings.

ZONES
1

DUST
ZONES
21

5
YEAR
WARRANTY



4,212 lumens 36W
7,380 lumens 60W

KEY FEATURES:

- AC 100-277V ~ 50/60Hz
- Low-profile, lightweight design
- High aluminium housing
- Impact resistant diffused lens
- Stainless steel bracket for ceiling mount
- Professional light distribution, uniformed illumination
- Single-ended feed-through cable or double ended optional
- Temperature class: T1 to T6
- Standard 6-12KV surge protection

36W



4,212
LUMENS

DIMENSIONS
1281x126
x88mm

4.5
KG

PRODUCT CODE: NSSAFA-AC-FLO-LIN-685

60W



7,380
LUMENS

DIMENSIONS
1281x126
x88mm

7.5
KG

PRODUCT CODE: NSSAFA-AC-FLO-LIN-1281



100-
277V
AC

IP66
RATING

CERTIFICATION:

- ATEX Zone 1 & 21 and 2 & 22
- Ex II 2 G Ex emb IIC T6 Gb
- EX II 2 D Ex tb IIIC 80°C Db IP66

CE

RoHS

Ex